



Description

Use in the main control room to realize the one-way broadcasting (spot, separate zone, or all zones) and dial-up intercom communication.

Features

- * Desktop mic, exquisite appearance and strong modern design.
- * 3.4-inch LCD screen, humanized operation interface.
- * With number and function keys, simple operation on broadcasting to any terminal or separated zones.
- * IR remote receiver is optional, all the operation can be realized by remote control.
- * Built-in 1W full frequency monitors speakers, the sound clear and resonant.
- * Support hands-free calls and receive the broadcasting.
- * Support 1 CH local line input, 1CH AUX input, connects with power amplifier outside.
- * DC 12V power supply.

Specifications

Model	T-6702
Network Input	Standard RJ45 input
Protocol Support	TCP/IP, UDP, IGMP (group broadcasting)
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transmit Speed	10Mbps
Audio Mode	16 digit stereo CD tone
Frequency Output	20Hz~16KHz
THD	≤ 0.3%
S/N	> 70dB
Aux Line Voltage Input	400mV Industrial standard screw terminals
Sources Voltage Output	775mV Industrial standard screw terminals
Source Impedance Output	1KΩ
Working Temperature	-20°C~+60°C
Working Humidity	10%~90%
Power Consumption	≤ 10W
Power Supply	DC12V
Dimensions	200x145x48.5mm
Weight	0.5Kg

Rear Panel

