



Applications

Being placed in the main control room for one-way broadcasting (point to point, zone or all zone) and dial-up two-way communication

Features

- * Desktop microphone type, with exquisite appetence, elegant craft and modern design
- * 3.4 inch LCD, with user-friendly human-machine interface.
- * With numeric keys, function keys to call any terminal, easy to operate.
- * With two-way intercom, realizing 2-way intercom from IP terminals to IP terminals.
- * Assistance bell signals tips; one touch to receive help, intercom, realizing fast connection.
- * Support infrared remote control receiver, with a remote controller to complete all operations.
- * Built-in 1W full-range monitor speakers with clear and loud sounds.
- * Support hands-free calls and broadcast receiving.
- * Support local one line input and one line audio auxiliary output; externally connect to
- * 12V DC power interface.

Specifications

Model	T-6702(D)
Network Interface	Standard RJ45
Support Agreement	TCP/IP, UDP, IGMP(multicast)
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio Mode	16-bit stereo CD sound quality
Output Frequency	20Hz~16KHz
THD	≤ 0.3%
S/N Ratio	>70dB
Auxiliary Line Input Level	400mV industry-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Impedance	1KΩ
Operating Temperature	-20℃~+60℃
Operating Humidity	10%~90%
Power Consumption	≤ 10W
Power Supply	DC12V
Dimensions	200x145x48.5mm
Weight	0.5Kg

Rear Panel

