

# IP PA & Intercom Network Adapter(with Amplifier) T-6705(D)



## Specifications

Model	T-6705(D)
Network Interface	Standard RJ45 input
Support Agreement	TCP/IP, UPP, IGMP (multicast)
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio Mode	16-bit stereo CD sound quality
Output Frequency	20Hz~16KHz
Harmonic Distortion	≤ %3
S/N Ratio	>70dB
Speaker Output Impedance and The Rated Power	4Ω , 1x10W industry-standard compression terminals
Auxiliary Line Input Level	400mV industry-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Impedance	1KΩ
Operating Temperature	-20℃~+60℃
Operating Humidity	10%~90%
Power Consumption	≤ 18W
Power Supply	~110V/60Hz or ~230V/50Hz
Dimensions	220x157x37mm
Weight	1.25Kg

## Applications

The Wall Mount IP Network Emergency Station is wall-mount type that suitable for dial-up intercom communication or background music broadcast.

## Features

- \* Wall-mount type; with symmetry and graceful body.
- \* 3.4 inch LCD; user-friendly human-machine interface.
- \* With numeric keys, function keys to call any terminal, easy and quick to operate.
- \* With two-way intercom, realizing 2-way intercom from IP terminals and IP terminals..
- \* With infrared remote control receiver; with a remote controller to complete all operations.
- \* Built-in 10W power amplifier, fixed impedance out put, externally connects to speakers.
- \* Support hands-free calls and broadcast receiving.
- \* Support local microphone, line input, volume adjustment.
- \* Audio auxiliary output, external power amplifier expansion.
- \* With AC220V ± 10% AC power interface.

## Rear Panel

