



Applications

The IP Network Emergency Station is suitable for indoor and outdoor embedded installation. It is suitable for dial-up two-way intercom communication.

Features

- * Rectangular embedded design, elegant keys, simple appearance with elegant lines and craft
- * With numeric keys, function keys to call any of the terminal, easy to operate.
- * With two-way intercom, realizing 2-way intercom from IP terminals and IP terminals.
- * Built-in microphone. Built-in 10W full-range monitors speakers with clear and loud sounds
- * Support local emergency button signal.
- * Support local electronic door locks, and local alarm indicator (select 1 from 2).
- * Support hands-free calls and broadcast receiving.
- * Support local one line input; one line audio auxiliary output, externally connect to amplifiers.

Specifications

Model	T-6706(D2)
network interface	Standard RJ45 input
Support Agreement	TCP/IP, UDP, IGMP(multicast)
Audio Format	MP3/MP2
sampling rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio mode	16-bit stereo CD sound quality
Output frequency	20Hz~16KHz
THD	≤ 0.3%
Signal to noise ratio	> 70dB
Auxiliary Line Input Level	400mV dusty-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Level	1KΩ
Operating temperature	-20℃~+60℃
Operating Humidity	10%~90%
Power consumption	≤ 15W
Power Supply	DC12V
Dimensions	240 × 115 × 50mm
Weight	1kg

Connections

