



Applications

The IP Network Emergency Station is suitable for indoor and outdoor embedded installation. It is suitable for dial-up two-way intercom communication

Features

- * Rectangular embedded design, with elegant appearance and craft
- * With 2.8 inch LCD liquid crystal display; user-friendly human-machine interface.
- * With numeric keys, function keys to call any of the terminal, easy to operate.
- * With two-way intercom, realizing 2-way intercom from IP terminals and IP terminals.
- * Support infrared remote control receiver, with a remote controller to complete all operations.
- * Support local emergency button signal.
- * Support local electronic door locks, and local alarm indicator (select 1 from 2).
- * Built-in microphone. Built-in 10W full-range monitors speakers with clear and loud sounds
- * Support hands-free calls and broadcast receiving.
- * Support local one line input and one line audio auxiliary output; externally connect to amplifier
- * 12V DC power interface

Specifications

Model	T-6712(D2)
network interface	Standard RJ45 input
Support Agreement	TCP/IP, UDP, IGMP(multicast)
Audio Format	MP3/MP2
sampling rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio mode	16-bit stereo CD sound quality
Output frequency	20Hz~16KHz
THD	≤ 0.3%
Signal to noise ratio	> 70dB
Auxiliary Line Input Level	400mV industry-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Impedance	1KΩ
Operating temperature	-20℃~+60℃
Operating Humidity	10%~90%
Power consumption	≤ 18W
Power Supply	DC12V
Dimensions	240 × 115 × 50mm
Weight	1kg

Connections

