

5 Zones Mixer Amplifier TI-240B



240W 100V 5 zone

Descriptions

The basic public address 5 zone mixer amplifiers have power ratings 240W.

They are featured of 3 balanced microphone inputs, 2 aux inputs and 2 EMC inputs.

Priority muting is achieved via EMC1-2 for overriding other inputs except Mic1 on front panel.

Individual gain controls are provided for Mic 1-3 and Aux 1-2, bass and treble controls and master volume control are provided for overall tone control.

70V, 100V and low impedance 4-16ohms speaker outputs are provided.

Extensive protection from short-circuit, overload and high temp.

Features

- * Mixer amplifier for paging and background music system
- * Rated power 240W
- * 2U rack mount (less than 350W) and 3U rack mount design
- * 70V, 100V and low impedance 4-16ohm speaker output
- * 5 zone and all zone speaker terminals
- * Three balanced Mic inputs
- * Mic 1(phone jack) with VOX priority and VOX level on front panel
- * Mic 2-3 by XLR type on rear panel with phantom power
- * Two Aux Inputs and 2 line inputs for spare use
- * Two EMC priority inputs
- * EMC1 has priority over all inputs except MIC1
- * Mic 1-3, Aux 1-2 and master volume controls and bass/treble tone control
- * Short circuit, overload and high temp protection


Optional

- * DC 24V available on less than 500W models
- * Panel with/without handhold
- * Faults monitoring module, it can output short circuit signal to achieve main/spare amplifier switch

Specifications

Model	TI-240B
Rated Power Output	240W
Speaker Outputs	70V, 100V & 4~16Ω
Input Sensitivity & Impedance	MIC 1, 2, 3: 5mV/600Ω , Unbalanced phone jack input MIC 2, 3: ± 2.5mV/2KΩ , Balanced XLR input MIC 2, 3: 775mV/10KΩ , Unbalanced RCA input AUX 1, 2: 350mV/10KΩ , Unbalanced RCA input EMC: 775mV/10KΩ , Unbalanced RCA input
Output Sensitivity & Impedance	MIX OUT: 1000mV/470KΩ , Unbalanced RCA output
Tone	Bass: ± 10dB at 100Hz Treble: ± 10dB at 10KHz
Frequency Response	50Hz~16KHz(+1dB, -3dB)
S/N Ratio	MIC 1, 2, 3: 66dB; AUX 1, 2: 80dB
THD	Less than 0.5% at 1KHz, 1/3 rated power
Muting Function	MIC 1 overrides other input signals with 0-30dB attenuation
Tone Control	± 2.5mV~ ± 75mV at 30dB
Crosstalk	≤ 50dB
Phantom Power	+48V, with LED indicator
Cooling	Fan automatically start up when temp reaches 55°C
Protection	High temp, overload & short-circuit
Power Supply	~110V/60Hz or ~230V/50Hz or DC 24V
Power Consumption	400W
Weight	17Kg
Dimensions	484×385×88mm
Finish	Panel: aluminum plate, black Case: steel plate, black

Rear Panel



Connections

