

Features

- * With the 2U chassis, High integration, modular design.
- * The 8 main 1 Preparation amplifier automatic backup switcher
- * Real time power amplifier state detection, and with different colors to indicate the LED.
- * Real time speaker bus return open circuit, circuit breaker, ground fault detection.
- * A power-off signal through.
- * 8 into 8 balanced audio input and output.
- * The device is closed and the power, audio input and output through.
- * Maximum support eight address code.

Specifications

Model	T-6281
AC Power Supply	
Power Supply	~110V/60Hz or ~230V/50Hz
Maximum Current	0.3 A (Does not include the 4 wire cut off power output)
Specification of Fuse	250V/1A, Slow type
Power Waste	48W
Performance Index	
Communication Mode	TCP/IP
Communication Interface	Dual RJ45 interface
Parallel Signal Input/Output	
Distortion	< 1% (Rated output power), 1kHz
Frequency Response	80Hz~20kHz
Sensitivity	Balance 385mV
Impedance	10k Ω
Signal to Noise Ratio	>70dB
Cooling Method	Passive cooling
Mechanical Index	
Size	484 x 357 x 88 mm (19 inches wide, 2U)
Net Weight	7.8KG
Installation	19 inch cabinet
Color	Black
Environmental Requirements	
Operating Temperature	+5°C ~ +40°C
Storage Temperature	-20°C ~ +70°C
Relative Temperature	<95% (Without condensation)

Rear Panel

