



Features

- * Power outputs: 2x80W, 2x120W and 2x240W.
- * Built-in 20 bytes DSP.
- * Built-in delay, repeat, echo and reverb features.
- * Separate volume control for echo & reverb.
- * 3 mic inputs with bass, treble and gain control, Mic1 with VOX priority.
- * 4 aux inputs, Aux input automatic detection, with auto and manual selector.
- * Synchronized AV switch, Channel switch feature.
- * 10 levels of output level meters.

Specifications

Model	T-2120K
Rated Power Output	2x120W
Speaker Outputs	4~8 Ω
Inputs	MIC1, 2, 3: ±2.5mV/600 Ω - ±175mV/10K Ω , Balanced EMC: 775mV/10K Ω , Unbalanced DVD: 350mV/10K Ω , Unbalanced VCD: 350mV/10K Ω , Unbalanced BMG: 300mV/10K Ω , Unbalanced EFFECTOR IN: 350mV10K Ω , Unbalanced
Outputs	EFFECTOR OUT: 350mV470 Ω S.W (150Hz): 2.5V/470 Ω PRE: 1v ± 50mv/470 Ω REC: 200mV ± 20mv/470 Ω VIDEO: 1VP-P/75 Ω
Mic Tone	Bass: ± 10dB at 100Hz MID: ± 10dB at 2KHz Treble: ± 10dB at 10KHz
Music Tone	Bass: ± 10dB at 100Hz MID: ± 10dB at 2KHz Treble: ± 10dB at 10KHz
Effect	ECHO DELAY: 80ms-240ms; ECHO REPEAT: 1-12 REVERB DELAY: 0ms-100ms; REVERB REPEAT: 0.1s-2s
Frequency Response	EMC,DVD,VCD,BGM: 20HZ(± 3db)--20KHZ(± 3db) Mic: 50HZ(± 3db)--16kHZ(± 3db)
S/N Ratio	Mic: ≥ 65db Music: ≥ 70db
THD	Less than 0.1% at 1KHz, 1/3 rated power
Indicators	Power LED, Output level meter
Power Supply	~220V/50Hz
Power Consumption	400W
Dimensions	430x399x132mm
Weight	11.46Kg