



### Description

Control room where intercom and sound system is both required, it can be take as a intercom station to call any zone, receive intercom call from intercom panel and serve as one IP amplifier to receive and broadcast network sources. Moreover, it also have the basic PA system features: background music system, zone paging system and voice alarm system highest priority broadcast.

### Features

- \* Wall-mount design with emergency intercom hand-clip microphone
- \* 3.4 inch LCD with user-friendly English display
- \* With numeric keys, function keys to call any terminal, easy and quick to operate.
- \* With two-way intercom, realizing 2-way intercom from IP terminals and IP terminals..
- \* Built-in 10W low impedance power amplifier for loading 4Ω loudspeaker
- \* Support hands-free calls and broadcast receiving.
- \* Support local microphone, line input, volume adjustment.
- \* Audio auxiliary output, external power amplifier expansion.
- \* With AC220V ± 10% AC power interface

### Specifications

Model	T-6705(D)
Network Interface	Standard RJ45 input
Support Agreement	TCP/IP, UPP, IGMP
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transfer Rate	10/100Mbps
Audio Mode	16-bit stereo CD sound quality
Output Frequency	20Hz~16KHz
Harmonic Distortion	≤ 3%
S/N Ratio	> 70dB
Speaker Output Impedance and The Rated Power	4 Ω, 1x10W industry-standard compression terminals
Auxiliary Line Input Level	400mV industry-standard voltage wire terminals
Audio Output Level	775mV industry-standard voltage wire terminals
Audio Output Impedance	1K Ω
Mic Input	10mV
Operating Temperature	5°C ~ +40 °C
Operating Humidity	10%~90%
Power Consumption	≤ 18W
Power Supply	~110V/60Hz or ~230V/50Hz
Dimensions	220x157x37mm
Weight	1.25Kg

### Connections

