



Features

- * Install standard 19" cabinet.
- * Whole block double circuit, no connecting fault.
- * SMT, more reliable.
- * 4 or 8 mono in/out.
- * 4 stereo input, 4 foldback input.
- * Left and right main output, Two-bus output.
- * 2 aux sending, one is after the push bar.
- * Monitor function, for all input and output.
- * Independent switch for each +48 phantom power.
- * LED DJ Light.

Specifications

Model	TS-12P-2
Mono Input Channel (Mic or Line)	4 channels
Stereo Input Channels (Line)	4 pairs (8 mono channels)
Phantom Power	30V
Output	Two unbalanced and two balanced master outputs, one stereo 3.5mm earphone output, two mono 3.5mm earphone outputs, two Aux outputs, two ALT outputs and two Track outputs.
Frequency Response	20Hz-20k Hz, ± 0.5 dB
Max Mic Gain at Mono Mode	37.4 dB to 55.4dB, ± 3 dB
Max Line Gain at Mono Mode	36.8 dB to 47.4dB, ± 3 dB
Max Line Gain at Stereo Mode	10dB, ± 3 dB
Crosstalk	71dB at 1k Hz and 60dB at 20k Hz
S/N Ratio	79dB at 1k Hz
Balanced Master Output	25.6dB, ± 1.5 dB
Unbalanced Master & ALT Output	19.6dB, ± 1.5 dB
Unbalanced Aux Output	19.2dB, ± 1.5 dB
Bass/Mid/Treble Frequency Point	65 Hz, 2.8k Hz & 14k Hz
Frequency Deviation & Gain	<8%, ± 15 dB
Output Level Meter	+20dB, +10dB, +7dB, +4dB, +2dB, 0dB, -2dB, -4dB, -7dB, -10dB, -20dB & -30dB
Power Supply	AC 120V or 220V; 50-60Hz
The Dimension of External Power Supply	129x90x77mm
Product Dimension(WxDxH)	285x392x80mm
Net Weight	4.05kg
Shipping Dimension(WxDxH)	450x446x168mm
Gross Weight	8.8kg